



Media  
Feed

### Specifications

Label Dimensions (WxL)	<b>2.00"x2.00"</b> <b>50.8mm x 50.8mm</b>
Quantity Per Roll	1000/Roll
Core Size	3"
Outer Diameter	8" Max
Label Face	Thermal Transfer Paper
Adhesive	Permanent
Operating Temperature	0° F to 200° F
Liner	40# SCK
RFID Inlay	<b>Texas Instruments HF-I Inlay</b>
Memory	2K Bit; Read/Write
Quality Inspection Level	<b>100%</b>
Inlay Placement	<b>Centered +/- 1mm</b>
Wind direction	Face out

## PRF 22112

PRF 22112 is a high quality 2x2 thermal transfer smart label incorporating the Texas Instruments 45mm x 45mm HF-I ISO 15693 inlay. This smart label is the perfect solution for asset tracking and anti-counterfeiting. The label face provides premium thermal transfer barcode printing for high and medium speed RFID label printers. The adhesive system is designed for excellent adhesion to corrugated and paper and superior adhesion to plastics.

### Superior Quality. Competitive Price.

PLITEK's ISO 9001:2000 quality assurance system along with our unique automated smart label quality testing system enable us to supply the highest quality 13.56MHz smart labels in the market today. Strong relationships with leading RFID inlay suppliers and efficient manufacturing and quality processes enable us to supply the highest quality smart labels at a competitive price.

### Contact us today for a quote.

PLITEK  
69 Rawls Road  
Des Plaines, IL 60018

Phone: 1.800.966.1250  
Fax: 1.847.827.6733  
Email: [rfid@plitek.com](mailto:rfid@plitek.com)  
Web: [www.plitek.com](http://www.plitek.com)

*Specifications are subject to change. Product should be tested thoroughly under end-use conditions to ensure it meets the application requirements.*